







## EN 853 2SN

	SIZE									FERRULE
				R.O.D.	O.D.	MAX. W.P.	BURST PRESS.	MIN BEND RADIUS	WEIGHT	
	DN	dash	mm	mm	mm	bar	bar	mm	g/m	
3/16" Hose	5	3	4,8	11,3	13,3	415	1.650	89	315	M03400-03
R204 (1/4" Bore Hose)	6	4	6,4	12,7	14,7	400	1.600	100	360	M03400-04
5/16" Hose	8	5	7,9	14,3	16,3	350	1.400	114	400	M03400-05
R206 (3/8" Bore Hose)	10	6	9,5	16,7	18,7	330	1.320	127	510	M03400-06
R208 (1/2" Bore Hose)	12	8	12,7	19,8	21,8	275	1.100	178	620	M03400-08
5/8" Hose	16	10	15,9	23,0	25,0	250	1.000	200	715	M03400-10
R212 (3/3" Bore Hose)	19	12	19,0	27,0	29,0	215	860	240	955	M03400-12
R216 (1" Bore Hose)	25	16	25,4	34,8	36,8	165	650	300	1.320	M00920-16

<b>Continuous Service</b>	-40 /+100 °C
<b>Max Temperature</b>	125 °C

**Substrate:**

OIL RESISTANT SYNTHETIC RUBBER

**Reinforcement:**

TWO HIGH TENSILE STEEL BRAIDS

**Cover:**

ENVIRONMENT RESISTANT SYNTHETIC RUBBER

**Applicable Specs:**

EN 853 2SN

MANULI RUBBER INDUST

ISO 1436-1 2SN/R2AT

SAE 100 R2AT