



S-320



S-320 shown with Reinforcing rod

FEATURES

Light weight portable hydraulic cutter features :

- * New series (heavy duty, improved design)
- * Two stage pumping for rapid blade advance
- * Safety relief valve for overload protection
- * Guillotine type cutting for less jamming than shear type cutting
- * No set-up time required
- * Blades are easily replaceable
- * 180 degree swivel and latch type head allows easy cutting position

SPECIFICATIONS

Maximum handle load : 276 N
 Two stage pumping
 Relief valve is equipped
 Reservoir capacity : 202 cc
 Maximum opening : 35 mm
 Pumping cycles when no load : 20 times

Output force : 191 kN

SIZE

580 (L) mm

WEIGHT

12.0 kg

ACCESSORIES

Carrying bag

REMARKS

Cutting of piano wire is prohibited.

Cutting capacity

Wire rope 6 x7	: 32 mm
Wire rope 6 x12	: 32 mm
Wire rope 6 x 19	: 32 mm
Soft steel bar	: 25 mm
Reinforcing rod	: 25 mm
Cu strands	: 32 mm
Al strands	: 32 mm
ACSR	: 32 mm
Guy wire 1 x7	: 32 mm
Guy wire 1 x 19	: 32 mm
CCP cable	: N/A