sales@hydraulics2u.co.uk

NRV Non-Return Valves Valves

CHECK VALVE (CARBON STEEL)



■ INTERCHANGE: MHA RV SERIES, FASTER VU SERIES, STUCCHI VU SERIES, GEMELS VU SERIES, HOLMBURY CV SERIES

SPECIFICATIONS :

·Body: carbon steel
·Piston: carbon steel

·Spring: C98 material

·Standard crack: 0.35bar and~0.5bar(5psi~7.25psi)

·Various crack pressures optional:to 6.5bar(94.25psi)


·Surface treatment :Zinc plating and Cr 3⁺ Passivation

or Black Passivation


APPLICATIONS:

One-way valve for in-line use.

Suitable for any type of hydraulic system using liquids that are not highly viscous. The standard types are in zinc plated carbon steel and especially suitable for non-corrosive mineral based oils and liquids.



PERFORMANCE



Art.No	Body Size	Max. Working Pressure	A	С	СН	T
NRV-14	1/4"	700 bar	60	18.5	19	1/4"BSPP
NRV-38	3/8"	700 bar	70	23.5	24	3/8"BSPP
NRV-12	1/2"	500 bar	77	29.5	30	1/2"BSPP
NRV-34	3/4"	500 bar	90	35.5	36	3/4"BSPP
NRV-1	1"	500 bar	106	44.5	45	1"BSPP
NRV-114	1-1/4"	400 bar	125	54.5	55	1-1/4"BSPP
NRV-112	1-1/2"	320 bar	140	64.5	65	1-1/2"BSPP
NRV-2	2"	320 bar	160	74.5	75	2"BSPP

We offer a Full Range of Hydraulic Products from a comprehensive range of manufacturers to bring you the products and systems most suited to your applications

