



P-60



P-60 shown with 1,000 mm² copper cable

FEATURES

The P-60 portable hydraulic cutter head features :

- * Fast cutting with remote operation
- * Guillotine type cutting for less jamming than shear type cutting
- * It can be operated by any hydraulic pump with rated oil pressure of 68.5 Mpa (10,000 PSI)
- * Equipped with NPT 3/8" threaded Parker type high pressure coupler
- * Blades are easily replaceable
- * Lock pin type cutter head

SPECIFICATIONS

Maximum input pressure : 68.5Mpa

Oil volume required : 71 cc

Maximum opening : 60 mm

Output force : 79 kN

SIZE

410 (L) mm

WEIGHT

5.8 kg

ACCESSORIES

Carrying bag

REMARKS

Cutting of piano wire is prohibited.

Cutting capacity

| | |
|------------|---------|
| Cu strands | : 60 mm |
| Al strands | : 60 mm |
| CCP cable | : 60 mm |

| | |
|------------------|-------|
| Wire rope 6 x7 | : N/A |
| Wire rope 6 x12 | : N/A |
| Wire rope 6 x 19 | : N/A |
| Soft steel bar | : N/A |
| Reinforcing rod | : N/A |
| ACSR | : N/A |
| Guy wire 1 x7 | : N/A |
| Guy wire 1 x 19 | : N/A |