sales@hydraulics2u.co.uk

BK3L - 3 Way Ball Shut Off Valves


3-WAY HIGH PRESSURE BALL VALVE (CARBON STEEL)




Without Mounting Holes



With Mounting Holes





■ INTERCHANGE: PISTER BK3 SERIES, MHA BK3 SERIES, HYDAC KHB3K SERIES, CIOCCA CRHI3 SERIES, GEMELS GE3 SERIES, HOLMBURY HCV-3 SERIES

SPECIFICATIONS :

·Body: carbon steel

·Ball: stainless steel or carbon steel

·Handle: Zinc Alloy

Standard O-Rings: NBR

On request O-Rings: Viton, Neoprene, EPDM or

other seals.

·Ball seals: DELRIN (POM)

·Temperature Range: -20°C+100°C/-4°F+212°F

·Surface treatment :Zinc plating and Cr 3+

Passivation

or Yellow Passivation

APPLICATIONS:

Hydraulics, agricultural and mobile hydraulics stainless steel versions are used in chemical and petrochemical industry, painting industry.

Art .No.	Size	Max. Working Pressure	ΦLW	L1	L2	L3	Н	L4XG	L5	L6	L7	Т
BK3T-14	1/4"	500 bar	Ф6	69	40	152	78	26X4.5	29	33	47.5	1/4BSPP(NPT)
BK3T-38	3/8"	500 bar	Ф10	71	42	154	84	32X5.2	35	38	52	3/8BSPP(NPT)
BK3T-12	1/2"	500 bar	Ф13	82	48	159	86	37.5X6.5	38	40	59	1/2BSPP(NPT)
BK3T-34	3/4"	315 bar	Ф20	96	62	219	119	45X6.5	52	57	72	3/4BSPP(NPT)
BK3T-1	1"	315 bar	Ф25	113	66	228	128	55X8.5	61	65	85	1BSPP(NPT)
BK3T-114	1-1/4"	315 bar	Ф25	120	66	231	128	55X8.5	61	65	85	1-1/4BSPP(NPT)
BK3T-112	1-1/2"	315 bar	Ф25	130	66	236	128	55X8.5	61	65	118	1-1/2BSPP(NPT)

We offer a Full Range of Hydraulic Products from a comprehensive range of manufacturers to bring you the products and systems most suited to your applications

